



MATERIAL SAFETY DATA SHEET

Trade Name: Blue Streak™

Revision Date: 22-Dec-09

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: Blue Streak™
Chemical Family: Mixture
Product Use: Oil well drilling fluid additive
Emergency Telephone (24 hr.): (ChemTrec) 800-424-9300
Supplied by: HiTech Fluid Systems Ltd.
1800, 505 - 3rd Street S.W.
Calgary, AB T2P 3E6
Tel: 403.547.2906
Fax: 403.547.3129
www.hitechfluid.com

Revision Number: 9

HMIS Rating
Health: 2 **Flammability:** 1 **Physical Hazard:** 0 **PPE:** J

HMIS Key: 4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal Hazard. *Chronic effects - See Section 11. See Section 8 for Personal Protective Equipment recommendations.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Wt. %	Comments:
Alkyl ether sulfate, amino salt		10 - 30	No comments.
Propylene Glycol	57-55-6	1 - 5	No comments.
Amine Salt		1 - 5	No comments.
2-Propanol, 1-amino	78-96-6	1 - 5	No comments.
Modified carbohydrate		1 - 5	No comments.
Water	7732-18-5	60 - 100	No comments.

3. HAZARDS IDENTIFICATION

Emergency Overview: Warning! May cause severe eye, skin and respiratory tract irritation.

Canadian WHMIS:
UN PIN No: Not regulated **WHMIS Class:** D2B

Physical State: Liquid **Odor:** Alcohol **Color:** Clear-Brown

Potential Health Effects:

Acute Effects
Eye Contact: May cause severe eye irritation.
Skin Contact: May cause severe skin irritation.
Inhalation: Vapors and mists may be irritating to severely irritating if inhaled.
Ingestion: May cause gastric distress, nausea and vomiting if ingested.

Carcinogenicity & Chronic Effects: See Section 11 - Toxicological Information.

Routes of Exposure: Eyes. Dermal (skin) contact. Inhalation.

Target Organs/Medical Conditions Aggravated by Overexposure: Eyes. Skin. Respiratory System

MATERIAL SAFETY DATA SHEET

Trade Name: **Blue Streak™**

Revision Date: 22-Dec-09

Page 2/5

4. FIRST AID MEASURES

Eye Contact:	Promptly wash eyes with lots of water while lifting eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.
Skin Contact:	Wash skin thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if any discomfort continues.
Inhalation:	Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion:	Dilute with 2-3 glasses of water or milk, if conscious. Never give anything by mouth to an unconscious person. If signs of irritation or toxicity occur, seek medical attention.
General Notes:	Persons seeking medical attention should carry a copy of this MSDS with them.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: F (C):	>200F (>93C)
Flammable Limits in Air - Lower (%):	ND
Flammable Limits in Air - Upper (%):	ND
Auto Ignition Temperature: F(C)	ND
Flammability Class:	IIIB
Other Flammable Properties:	ND
Extinguishing Media:	Water fog, carbon dioxide, foam, dry chemical.

Protection of Fire-Fighters

Special Fire-Fighting Procedures:	Do not enter fire area without proper personal protective equipment, including NIOSH/MSHA approved self-contained breathing apparatus. Evacuate area and fight fire from a safe distance. Water spray may be used to keep fire-exposed containers cool. Keep water run off out of sewers and waterways.
Hazardous Combustion Products:	Oxides of Carbon. Sulfur. Nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Use personal protective equipment identified in Section 8.
Spill Procedures:	Evacuate surrounding area, if necessary. Keep personnel removed and upwind of spill. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Shut off leak if it can be done safely. Contain spilled material. Absorb in vermiculite, dry sand or earth. Place into containers for disposal.
Environmental Precautions:	Do not allow to enter sewer or surface and subsurface waters. Waste must be disposed of in accordance with federal, state and local laws. In the U.S., for products with reportable quantity (RQ) components - if the RQ is exceeded, report to National Spill Response Office at 1 800 424 8802.

7. HANDLING AND STORAGE

Handling:	Put on appropriate personal protective equipment. Avoid contact with skin and eyes. Avoid breathing vapors or spray mists. Use only in a well ventilated area. Wash thoroughly after handling..
Storage:	Store in dry, well-ventilated area. Keep container closed. Store away from sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

MATERIAL SAFETY DATA SHEET

Trade Name: **Blue Streak™**

Revision Date: 22-Dec-09

Page 3/5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits (TLV & PEL - 8H TWA):

Ingredient	CAS No.	Wt. %	ACGIH TLV	OSHA PEL	Other	Notes
Alkyl ether sulfate, amino salt		10 – 30	NA	NA	NA	None
Propylene Glycol	57-55-6	1 – 5	NA	NA	AIHA WEEL: 50 ppm (total); 10 mg/m ³ (aerosol	None
Amine salt		1 – 5	NA	NA	NA	None
2-Propanol, 1-amino	78-96-6	1 – 5	NA	NA	NA	None
Modified carbohydrate		1 – 0	NA	NA	NA	None
Water	7732-18-5	60 - 100	NA	NA	NA	None

Engineering Controls:

Local exhaust ventilation as necessary to maintain exposures to within applicable limits.

Personal Protection Equipment

Eye/Face Protection:

Wear chemical safety goggles.

Skin Protection:

Wear appropriate clothing to prevent repeated or prolonged skin contact. Wear chemical resistant gloves such as nitrile or neoprene.

Respiratory Protection:

If exposed to particulates/aerosols: Use at least a NIOSH-approved N95 half-mask disposable particulate respirator. In work environments containing oil mist/aerosol use at least a NIOSH-approved P95 half-mask disposable or reuseable particulate respirator.

If exposed to organic vapors: Use a NIOSH/MSHA-approved organic vapor respirator. CCROV: CCR with organic vapor cartridge.

A NIOSH/MSHA approved respirator with ammonia/methylamine cartridges should be used to protect against ammonia or amine inhalation exposure.

Refer to Exposure Limits table (Section 8) for component specific respiratory protection recommendations.

General Hygiene Considerations:

Work clothes should be washed separately at the end of each work day. Disposable clothing should be discarded, if contaminated with product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Clear
Odor:	Alcohol
Physical State:	Liquid
pH:	3.5
Specific Gravity (H ₂ O = 1):	1.01
Solubility (Water):	Soluble
Flash Point: F (C):	>200F (>93C)
Melting/Freezing Point:	ND
Boiling Point:	ND
Vapor Pressure:	ND
Vapor Density (Air=1):	ND
Evaporation Rate:	ND
Odor Threshold(s):	ND

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable

Conditions to Avoid:

Keep away from heat, sparks and flame.

Materials to Avoid:

Oxidizers. Bases.

MATERIAL SAFETY DATA SHEET

Trade Name: **Blue Streak™**

Revision Date: 22-Dec-09

Page 4/5

Hazardous Decomposition Products: For thermal decomposition products, see Section 5.

Hazardous Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

Component Toxicological Data: Any adverse component toxicological effects are listed below. If no effects are listed, no such data were found.

Ingredient	CAS No.	Acute Data
Propylene Glycol	57-55-6	Oral LC50: 20 - 34 g/kg (rat); Dermal LC50: >10 g/kg (rabbit)
2-Propanol, 1-amino	78-96-6	Oral LC50: 1715 mg/kg (rat); Dermal LC50: 1640 ul/kg (rabbit)

Ingredient	Component Toxicological Summary
Modified carbohydrate	This component is a derivative of a natural protein. The natural protein has been reported to cause respiratory sensitization (asthma, rhinitis) in humans. This component contains less of the natural protein. It, therefore, is expected to have a much lower risk of causing respiratory sensitization. (Vendor MSDS)

Product Toxicological Information: No toxicological data is available for this product.

12. ECOLOGICAL INFORMATION

Ingredient	CAS No.	Acute Data
Propylene Glycol	57-55-6	LC50 24H: >5000 mg/l (goldfish); LC50 48G: >10,000 mg/l (guppy); EC50 30M: 710 mg/l (Photobacterium phosphoreum); EC50 48H: <10,000 mg/l (water flea)
2-Propanol, 1-amino	78-96-6	LC50 24H: >5000 mg/l (goldfish); LC50 96H: LC50 96H: >220 <46- mg/l (Leuciscus idus); 2520 mg/l (fathead minnow); EC/LC50 48H: 23 mg/l (daphnae); EC50 5M: 27.2 mg/l (Photobaterium phosphoreum)

Product Ecotoxicity Data: Contact MASI's Environmental Affairs Department for available product ecotoxicity data.

Biodegration: ND

Bioaccumulation: ND

Octanol/Water Partition Coefficient: ND

13. DISPOSAL CONSIDERATIONS

Waste Classification: ND

Waste Management: Under U.S. Environmental Protection Agency (EPA) Resource Conservations and Recovery Act (RCRA), it is the responsibility of the user to determine at the time of disposal, whether the product meets RCRA criteria for the hazardous waste. This is because product uses, transformations, mixtures, processes, etc., may render the resulting materials hazardous. Empty containers contain residues. All labeled precautions must be observed.

Disposal Method: Recover and reclaim or recycle, if practical. Should this product become a waste, dispose of in a permitted industrial landfill. Ensure that the containers are empty by the RCRA criteria prior to disposal in a permitted industrial landfill.

14. TRANSPORT INFORMATION

U.S. DOT

Shipping Description: Not regulated for transportation by DOT, TDG, IMDG, ICAO/IATA.

TDG (Canada):

Shipping Description: Not regulated

UN PIN No: Not regulated

IMDG

Shipping Description: Not regulated

ICAO/IATA

Shipping Description: Not regulated.

MATERIAL SAFETY DATA SHEET

Trade Name: **Blue Streak™**

Revision Date: 22-Dec-09

Page 5/5

15. REGULATORY INFORMATION

U.S. Federal and State Regulations

SARA 311/312 Hazard Categories: Immediate (acute) health hazard.

SARA 302/304, 313; CERCLA RQ, California Proposition 65: Note: If no components are listed below, this product is not subject to the referenced SARA and CERCLA regulations and is not known to contain a Proposition 65 listed chemical at a level that is expected to pose a significant risk under anticipated use conditions.

International Chemical Inventories

Australia AICS - Components are listed or exempt from listing.
Canada DSL - Components are listed or exempt from listing.
China Inventory - Components are listed or exempt from listing.
European EINECS - Components are listed or exempt from listing.
Japan METI ENCS - Components are listed or exempt from listing.
Korea TCCL ECL - Components are listed or exempt from listing.
Philippine PICCS - Components are listed or exempt from listing.
U.S. TSCA - Components are listed or exempt from listing.
U.S. TSCA - No components are subject to TSCA 12(b) export notification requirements.

Canadian Classification:

Controlled Products Regulations Statement: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Class: D2B

16. OTHER INFORMATION

The following sections have been revised: 1

NA - Not Applicable, ND - Not Determined.

Disclaimer:

MSDS furnished independent of product sale. While every effort has been made to accurately describe this product, some of the data are obtained from sources beyond our direct supervision. We can not make any assertions as to its reliability or completeness; therefore, user may rely on it only at user's risk. We have made no effort to censor or conceal deleterious aspects of this product. Since we cannot anticipate or control the conditions under which this information and product may be used, we make no guarantee that the precautions we have suggested will be adequate for all individuals and/or situations. It is the obligation of each user of this product to comply with the requirements of all applicable laws regarding use and disposal of this product. Additional information will be furnished upon request to assist the user; however, no warranty, either expressed or implied, nor liability of any nature with respect to this product or to the data herein is made or incurred hereunder.