



## Product Information

---

### TechWet

#### GENERAL DESCRIPTION

TechWet is a concentrated oil wetting agent that also acts as a secondary emulsifier to increase emulsion stability. TechWet is designed to work with TechWet to oil wet solids that enter the system from the drilling operation, as well as weighting material added to increase fluid densities.

TechWet is an extremely efficient wetting additive that will control excessive increases in viscosity due to wettability issues.

#### FEATURES AND BENEFITS

- ✓ Controls excessive increases in viscosity due to wettability issues
- ✓ Concentrated oil wetting agent
- ✓ Improves emulsion stability as a secondary function
- ✓ Temperature stable to 150°C
- ✓ Ease of use

#### RECOMMENDED TREATMENT

TechWet is typically applied neat. The treating range is normally 1 - 5L/m<sup>3</sup>. Factors such as dispersion time, concentration of solids, and type of oil will affect the treatment range. Detailed application techniques and volumes are available from our technical representatives.

#### TYPICAL PHYSICAL PROPERTIES

Appearance	Liquid, Clear Brown to Dark Brown
Pour Point	< -20°C
Flash Point	> 80°C
Density @ 15°C	0.90 - 0.96 kg/L

#### HANDLING

This product may require special precautions in handling and/or use because of toxicity, flammability or other considerations.

Refer to MSDS information for specific precautions and handling.

#### AVAILABILITY

TechWet is available in 205 litre returnable drums and in bulk quantities from HiTech Fluid Systems Ltd.